



THE INDUSTRY'S PREMIER LOW VOLTAGE LIGHTING TRANSFORMER

600^{WATT}
MAGNETIC



FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- AVAILABLE WITH PRIMARY LINE CORD.
- BUILT IN THE USA TO THE HIGHEST STANDARDS

REQUIREMENTS

- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA AND CE REQUIREMENTS
- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411

SPECIFICATIONS

PART NUMBER	PRIMARY VOLTAGE	OUTPUT VOLTAGE	BREAKERS	FREQUENCY	DIMENSIONS	WEIGHT
CLASS 1						
1102-12	120VAC-5.25A MAX	12VAC-2x25A MAX	2x25 A	60 Hz	8.25" x 5.25" x 5.5"	22 LBS.
1102-24	120VAC-5.25A MAX	24VAC-2x25A MAX	1x25 A	60 Hz	8.25" x 5.25" x 5.5"	22 LBS.
1130-12	277VAC-5.25A MAX	12VAC-2x25A MAX	2x25 A	60 Hz	8.25" x 5.25" x 5.5"	22 LBS.
1130-24	277VAC-2.4A MAX	24VAC-25A MAX	1x25 A	60 Hz	8.25" x 5.25" x 5.5"	22 LBS.