



THE INDUSTRY'S PREMIER LOW VOLTAGE LIGHTING TRANSFORMER

300^{WATT}
MAGNETIC



FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- AVAILABLE WITH PRIMARY LINE CORD.
- BUILT IN THE USA TO THE HIGHEST STANDARDS

REQUIREMENTS

- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA AND CE REQUIREMENTS
- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411

SPECIFICATIONS

PART NUMBER	PRIMARY VOLTAGE	OUTPUT VOLTAGE	BREAKERS	FREQUENCY	DIMENSIONS	WEIGHT
CLASS 1						
1101-12	120VAC-2.75A MAX	12VAC-25A	1x25 A	60 Hz	6.75" x 5" x 4.75"	13 LBS.
1101-24	120VAC-2.75A MAX	24VAC-12.5A MAX	1x12 A	60 Hz	6.75" x 5" x 4.75"	13 LBS.
1105-12	277VAC-2.75A MAX	12VAC-25A MAX	1x25 A	60 Hz	6.75" x 5" x 4.75"	13 LBS.
1105-24	277VAC-1.2A MAX	24VAC-12.5A MAX	1x12 A	60 Hz	6.75" x 5" x 4.75"	13 LBS.
CLASS 2						
1123	120VAC-1.3A MAX	12VAC-5A MAX	5x5 A	60 Hz	6.75" x 5" x 4.75"	13 LBS.
1124	120VAC-1A MAX	24VAC-4A MAX	3x4 A	60 Hz	6.75" x 5" x 4.75"	13 LBS.