

LOW VOLTAGE REMOTE TRANSFORMERS

Designed for Low Voltage Lighting, Made in USA

Features

- Epoxy encapsulated for quiet, cool operation.
- Powder painted case for maximum protection.
- Thermostat Protected Primary windings.
- Circuit breaker protects secondary windings.
- Electrostatic grounded shield between primary and secondary windings for cool, safe operation.
- Easy opening case with knockouts for hard wiring.
- Primary 5% boost tap provided to compensate for voltage drop on long runs of 20 feet or more.
- Labeling and complete operating instructions supplied.
- All units are UL Listed to U.S and Canadian safety standards.



12 Volt

Part No.	Wattage	Length*	Width	Depth	Weight
20100-0010	Single 100W	8.5"	3.5"	3.5"	5 Lbs.
20150-0010	Single 150W	8.5"	3.5"	3.5"	7 Lbs.
20300-0010	Single 300W	8.5"	4"	3.5"	10 Lbs.
20500-0012	Dual 250W, 500W Total	11"	4"	4.5"	14 Lbs.
20600-0012	Dual 300W, 600W Total	11"	4"	4.5"	14 Lbs.

24 Volt

Part No.	Wattage	Length*	Width	Depth	Weight
20100-0026	Single 100W	8.5"	3.5"	3.5"	5 Lbs.
20150-0026	Single 150W	8.5"	3.5"	3.5"	7 Lbs.
20250-0026	Single 250W	8.5"	4"	3.5"	10 Lbs.
20300-0026	Single 300W	8.5"	4"	3.5"	11 Lbs.
20500-0026	Single 500W	8.5"	4"	4.5"	13 Lbs.
20600-0026	Single 600W	11"	4"	4.5"	14 Lbs.

*Length includes Brackets

